

Upholstery Fabric – 4585 / 4591

NFPA 260-2013 - Standard Methods of Test and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture

The material submitted is an NFPA 260 Class I cover fabric when tested in accordance with NFPA 260, Fabric Classification Test Method.

| Specimen # | Vertical Char Length (mm) |
|------------|---------------------------|
| 1 | 11 |
| 2 | 10 |
| 3 | 10 |

Classification:

Class 1 - This class includes all fabrics which exhibit a vertical char of less than 45 mm on each of the three replications when subjected to the fabric classification test of NFPA 260, Section 6.1.

AATCC 116-13 – Colorfastness to Crocking: Rotary Vertical Crockmeter Method

Staining Evaluation Method: Gray Scale for Staining

| Specimen/Sample | Original | |
|-----------------------------|----------|-----|
| | Dry | Wet |
| Upholstery Fabric – 4585-12 | 4.5 | 4.5 |

RATING SYSTEM

- Grade 5, Negligible Color Staining
- Grade 4, Slight Color Staining
- Grade 3, Noticeable Color Staining
- Grade 2, Considerable Color Staining
- Grade 1, Excessive Color Staining

For and on behalf of
Intertek Products Group North America:

Edwin Serrano
Account Manager

Intertek North America

545 E Algonquin Road, Suite F
Arlington Heights, Illinois 60005
Telephone: 847-871-1020 Fax: 847-439-6156

