

**Test Performed As Requested by Client:**

**TEST RESULTS:**

**1. 16 CFR 1640: Standard for the Flammability of Upholstered Furniture, CA TB 117: 2013 - Smolder Resistance of Materials Used in Upholstered Furniture**  
 Section 1 – Cover Fabric Test

**Sample Description:** Upholstery - (6507Stellula)

Initial Test			
	Vertical Char Length (in)	Mock-up Specimen Continues to Smolder after 45 minutes	Mock-up Specimen Transitions to Open Flaming
Specimen 1	0.9	No	No
Specimen 2	0.9	No	No
Specimen 3	0.9	No	No

**Conclusion:**

The Sample submitted for testing **Passes** the requirements in 16 CFR PART 1640.5 Standard For The Flammability of Upholstered Furniture, California Technical Bulletin 117-2013  
 Section 1: Cover Fabric Test

**2. ASTM D5034-2021 - Breaking Strength and Elongation of Textile Fabrics**

Grab Test

Size of Clamps: 1" x 1" (Front); 1" x 3" (Back)

Sample Condition: Conditioned

SPECIMEN		SAMPLE
Upholstery - (6507- Fabric)		
BREAKING FORCE lbf		
WARP	AVERAGE	434.1
WEFT	AVERAGE	190.8