

**Test Performed As Requested by Client:**

**1. Standard for the Flammability of Upholstered Furniture (16 CFR 1640)**

**Smolder Resistance of Materials Used in Upholstered Furniture (CA TB 117-2013)**

Section 1 – Cover Fabric Test

**Sample Description:** Rosette 2327 / Tulliana 2328 – Color: 2328-02

**Initial Test Results:**

	Vertical Char Length (in)	Mock-up Specimen Continues to Smolder after 45 minutes	Mock-up Specimen Transitions to Open Flaming	Specimen Result
Specimen 1	0.6	No	No	Pass
Specimen 2	0.7	No	No	Pass
Specimen 3	0.6	No	No	Pass

**Requirements:**

- A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - The mock-up test specimen continues to smolder after the 45 minute test duration.
  - A vertical char length of more than 1.8 inches (Section 1), 2.0 inches (Section 2), or 1.5 inches (Sections 3 & 4), develops on the cover fabric.
  - The mock-up test specimen transitions to open flaming.
- The sample passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
- If more than one initial specimen fails, the sample fails the test.
- If any one of the three initial specimens fails, repeat the test on additional three specimens.
- If all three additional specimens pass the test, the sample passes the test. If any one of the additional three specimens fails, the sample fails the test.

**Conclusion: Pass** – The sample submitted for testing meets the requirements in 16 CFR PART 1640.5 Standard for the Flammability of Upholstered Furniture, California Technical Bulletin 117-2013

**Section 1: Cover Fabric Test**